



THULE



Le furgonature isothermiche **THULE** sono progettate e realizzate al fine di rispettare le normative vigenti per il trasporto di merce in regime di temperatura controllata. Specifica per la gamma di veicoli a tonnellaggio leggero, abbina doti di leggerezza, ottimo potere isolante, flessibilità e volume di carico.

Idonea per veicoli fino a 65 q.li, è ideale per il trasporto di prodotti freschi con temperatura fino a 0 °C. e prodotti congelati con temperatura fino a -20 °C.

DOTAZIONE DI SERIE

- Riquadro posteriore inox a U con due porte con chiusure incassate e cerniere in acciaio inox
- Tamponi paracolpi in gomma sotto porte
- Angoli esterni protetti da profilo in alluminio anodizzato
- Pavimento liscio colore grigio
- Impianto illuminazione interna
- Foro di scarico liquidi
- Fermaporte a molla sotto pianale
- Falso telaio in acciaio **zincato**
- Predisposizione per gruppo frigorifero

Isothermic bodies **THULE** are projected to respect the laws in force for the transportation of the cargo with the regulated temperature. Especially suitable for the range of the vehicles of the law tonnage, it is very light, has a perfect isolating power, flexibility and loading capacity. Fit for the vehicles up to 65 quintals, is ideal for the transportation of the fresh products with the temperature up to 0 °C. and frozen products with the temperature up to -20 °C.

STANDARD EQUIPMENT

- Stainless steel rear frame **U** profile with 2 doors with stainless steel hinges and recessed locks
- Rear rubber buffers under doors
- External aluminium anodized profile
- Smooth grey color floor
- Internal ceiling light
- Draininghole
- Spring doors stopper under floor
- **Galvanized** steel subframe
- Reinforcement for cooling unit

È possibile realizzare una furgonatura idonea alle necessità del cliente, con numerose personalizzazioni; quali trasporto di carne, pesce, roller distribuzione/ fiori, etc...

Is possible to realize the body adequate to the necessity of the client, with numerous personalization: f. e. meat and fish transportation, roller distribution/flowers etc...

SPESSORI	
Pavimento	100 mm
Tetto	100 mm
Fiancate	60/80 mm
Testata anteriore	100 mm
Porte posteriori	80 mm

THICKNESS	
Floor	100 mm
Ceiling	100 mm
Side walls	60/80 mm
Front wall	100 mm
Rear doors	80 mm

CLASSIFICAZIONE ATP	
Coefficiente K	< 0.40 W/m ² °C
Classe	Isotermico Rinforzato

ATP CLASSIFICATION	
K Coefficient	< 0.40 W/m ² °C
Type	IR

